

**stanok**

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy  
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39  
[www.stanok.it](http://www.stanok.it) - [info@stanok.it](mailto:info@stanok.it)



## FERMANT T40-2MT

The FERMANT 40-2M-T serves to seal thermoplastic tubes. It is used wherever small batch sizes or pilot batches are to be sealed in rational manner.

The range of application covers a wide area and extends from cosmetic articles, including medical and pharmaceutical products, to products in veterinary field.

The impulse time and contact pressure are continuously digitally selectable and can be adapted to the thickness of the type of tubes used in each case.

The tubes are passed through from bars before sealing. Two lifting magnets provide the required contact pressure and guarantee reliable sealing of the tubes.

This tube sealing device can be also supplied in stainless and acid resistant stainless steel.



### **A richiesta**

Tube magazine  
Stainless steel version  
Modification on request

## TECHNICAL DATA



### FERMANT T40-2MT

Sealing length (mm)	400
Sealing width(mm)	4
Distance between sealing bars (mm)	12
Connection	230V/50 Hz 115V/50 Hz (On request)
Weight	Kg. 40
Dimension without vertical stand (mm)	700x330x260
Material	Tubes



Technical alteration without prior notice.