

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



SMALL PACKER TM

Small Packer TM are film sealing units, which are specially equipped with funnel and other accessories. The unit is prepared with a holding device to bring the unit in an inclined position. Furthermore a working table with a shifting square, a funnel holder, and the minimum of one funnel is required.

The funnel has to be taken off, in order to pull the tubular film over. Then the funnel is put in place on the suspension.

The shifting square is matched on the size needed for the goods that are to be packed.

The unit is now prepared for optimal usage.

The goods to be packed are filled into the funnel and fall down on the shifting square.

Now the sealing impulse is released and the package is separated from the remaining film tube.

A possibility is to use more than just one funnel at a time in order to produce more than one package in one single working step.



Optional

Additional funnel
Lengthening of the worktable
Rolling off device

TECHNICAL DATA

SMALL PACKER TM401

Max sealing length (mm)	420
Sealing width (mm)	2 c.a
Opening bar (mm)	45
Sealable film thickness (mm)	2x0,20
Power supply	230V/50 Hz
Weight	Kg. 25
Dimension (mm)	600x295x175h
Usable film	PE and PP tubolar film

SMALL PACKER TM600

Max sealing length (mm)	600
Sealing width (mm)	2 c.a
Opening bar (mm)	45
Sealable film thickness (mm)	2x0,20
Power supply	230V/50 Hz
Weight	Kg. 30
Dimension (mm)	800x295x175h
Usable film	PE and PP tubolar film



Technical alteration without prior notice