

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



TM-L

TM-L are powerful film sealing units. They work without a pre-heating time and are designed for constant industrial use. The sealing bar is closed with one manual movement.

The welding time can be regulated to the bag's gauge.

Model TM-L is available in 2 different sizes: 400 and 600 mm.



Optional

- Holding magnet
- Holding magnets and double sided heating
- Hotwire
- Cutting device
- Roll holder

TECHNICAL DATAI

TM 400 L

Sealing length (mm)	400
Sealing width (mm)	3
Openig bars (mm)	45
Film thickness (mm)	2x0,20
Power supply	230V/50 Hz
Weight	Kg. 20
Dimension (mm)	60x295x175h
Material	PE, PELO, PEHD,PP, PVC

TM 600 L

Sealing length (mm)	600
Sealing width (mm)	3
Openig bars (mm)	45
Film thickness (mm)	2x0,20
Power supply	230V/50 Hz
Weight	Kg. 24
Dimension (mm)	800x295x175h
Material	PE, PELO, PEHD,PP, PVC



Technical alteration without prior notice.